FINE QUALITY STOVES

STOVE SPECIFICATIONS AND OPTIONS

Use this table to help you decide which ESSE model is best suited to your heating requirements, and preferred fuel type. Your local ESSE dealer will be happy to arrange a site visit to discuss your specific needs and answer any questions.

Fuel type

	Vista	200	Turnberry	Dragon	Furnesse	Montrose	500	Solo
MULTI-FUEL								
External riddling	●	○	●	●	○	○	●	
Overnight burning (*Suitable for continuous burning)	●	●	●	●	●*	●	●	
Pre heated secondary airwash	●	●	●	●	●	●	●	
Afterburn™ system	○	●	○	○	○	○	○	
Boiler model – domestic (optional)	●	○	●	●	○	○	○	
Boiler model – central heating (optional)	●	○	●	●	○	○	○	
Operating range (depending on fuel type and settings)	Up to 8kW/h	Up to 7.5kW/h	Up to 8kW/h	Up to 8kW/h	Up to 3kW/h	Up to 5.5kW/h	Up to 5.5kW/h	
GAS – Natural or LPG								
Piezo spark ignition	●		●	●		●	●	
Auto safety shut off	●		●	●		●	●	
Fuel effect (*Flueless only)	Coal		Coal	Coal		Coal	Coal/Logs*	
Additional room vents required**	None		None	None		None	None	
Suitable for class 1 or 2 flues (including precast)	●		●	●		●	●	
Heat output - max / min	4.7kW / 1.5kW		4.7kW / 1.5kW	4.75kW / 1.5kW		3.5kW	3.5kW	
Flueless with patented catalytic technology	○		○	○		○	●	
Thermostatically controlled	○		○	○		○	●	
OIL – 28 sec oil kerosene								
Built in draught stabiliser	●		●					
Realistic log burning flame pattern	●		●					
Heat output – max / min	7kW / 2kW		7kW / 2kW					
Glow plug electric ignition	●		●					
ELECTRIC								
Weight							16kg	40kg
Thermostatically controlled							●	●
Heat output							2kW	2.2kW
ALL STOVES								
Construction (*500 Electric)	Cast Iron	Steel/Cast iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron/mdf*	Cast Iron choice of 6 colours
Flue outlet (*top only on oil models)	Top or Rear*	Top or Rear	Top or Rear*	Rear Only	Class 1 chimney	Top or Rear	Top or Rear	○
Flue pipe diameter	5"(125mm)	5"(125mm)	5"(125mm)	5"(125mm)	5"(125mm)	5"(125mm)	5"(125mm)	○